


Engage every student as if they were still in class

The DL30 is a powerful distance learning tool that allows teachers to fully engage with their students no matter where they are learning. Specifically designed for the modern classroom, the DL30 enables teachers to fully move about the room while the camera automatically follows to engage both in-class and remote learners equally. Featuring AI Auto Tracking, 12X Optical Zoom, PoE+ with USB connectivity, the DL 30 allows teachers to focus on all students without worry.

Phy

guitar?

90



The DL30 utilizes advanced Artificial Intelligence (AI) which can be set to either Presenter Tracking or Zone Tracking. Presenter Tracking tracks the entire body, or half the body instead of just the face without the need to wear a lanyard. The camera does not rely on voice tracking which can confuse other cameras as to who to track in the classroom. Tracking even works if the teacher is wearing a PPE mask and remote students will never lose sight.



Privacy mode

In order to protect student and teacher privacy when the camera is not in use, the DL30 automatically rotates the camera head 90° downward so nothing can be viewed. When Privacy Mode is activated, the LED light will turn orange, indicating that the camera is no longer active, while it can be taken out of Privacy Mode with a short press of the power button.

Distance learning ready


The DL30 is fully compatible with all popular video conferencing platforms such as Zoom, Google Meet, Google Hangouts and Microsoft Teams to connect and stream professional quality videos or record and save your lessons for later reference.



12X optical zoom for superior clarity

The 2MP camera with 12X optical zoom outputs high definition and real-life video to keep remote students engaged. Compared with basic digital zoom which can be grainy and unclear, the 12X optical zoom clearly shows the finest details of physical demonstrations, whiteboard work, IFP content, science experiments, and any other curriculum content no matter where it is located in the room. Share real-life content with brilliant clarity for a true classroom experience no matter where your students are learning.





Intuitive and interactive software for teachers and IT managers

Enhance your distance learning and engage your remote students with CaptureShare, our interactive distance learning software that enables teachers to deliver engaging lessons for your students no matter where they are learning from. AVerPTZ Control Panel for iPad allows the teacher to control his or her camera from the iPad, while PTZ Management allows your IT staff to manage and maintain hundreds of cameras in the district from a single location.



Specifications

			Camera		
Image Sensor	1/2.8" 1080p Low Lux CMOS	WDR	Yes	Pan/Tilt Angles	Pan: ±170° Tilt: ±90°
Effective Picture Elements	2 Megapixels	White Balance	Auto, Manual	Pan/Tilt Speed (Manual) Pan: 1° to 90°/sec	
Output Resolutions	1080p/60 (IP Streaming & USB)	Optical Zoom	12X		Tilt: 7.85° to 45°/sec
		Digital Zoom	2X	Preset Speed	Pan: 120°/sec Tilt: 110.84°/sec
Minimum Illumination	0.5 Lux (IRE50, F1.6, 30fps)	Digital 20011			

S/N Ratio	>50 dB			: 84.1° (Wide) to 7.8° (Tele)	Preset Positions		10 (IR), 256 (IP & US	
Gain	Auto, Manual			: 76.5° (Wide) to 6.8° (Tele) : 47.3° (Wide) to 3.8° (Tele)	Camera Control - Interfaces		s IP, USB	
TV Lines	800 (Center), 600 (Corner)	Focal Length	f = 3.9	9 mm (Wide) to 46.8 mm (Tele)	Camera Control -	Protocols	VISCA (IP), CGI (IP),	
Shutter Speed	1/4 to 1/10,000 sec (60 Hz)1/3	Aperture (Iris)	F = 1.0	6 (Wide) to 2.8 (Tele)	Image Processing	g	Noise Reduction (2)	
Evenanura Control	to 1/10,000 sec (50 Hz)	Minimum Working Distance	0.3 m	(Wide), 1.5 m (Tele)	Power Frequencie	20	Flip, Mirror, WDR 50 Hz, 60 Hz	
Exposure Control	Auto, Manual, WDR	Distance			Fower riequencie		30 112, 00 112	
		AI	Auto Tra	cking Functions				
Tracking Modes	Presenter Mode, Zone Mode							
			A	Audio				
Channels	2ch Stereo	Codecs	AAC,	PCM	Sample Rates	AAC (48	8/32/16/8 KHz), PCM (48 KHz)	
			Int	terface				
Video Outputs	IP, USB	Audio Outputs	IP, US	ŝB	Audio Inputs	Mic in,	Line in	
			0	eneral				
David David Street and	40 110 000V/t- D0 10V/04	No. 194	9		Damata Qanturl		Informed	
Power Requirement	AC 110-220V to DC 12V/2A	Net Weight		1.62 (±0.1) kg	Remote Control		Infrared	
Power Consumption PoE	12W PoE+	Application		Indoor N/A	Operating Conditions		Temperature: 0°C to 40°C Humidity: 20% to 80%	
Dimensions (W x H x D)	PoE+ 158.8 x 200.0 x 162.2 mm	Tally Lamp Security		N/A Kensington Slot	Storage Conditions		Temperature: -20°C to 60°C	
Dimensions (W X TI X D)	130.0 x 200.0 x 102.2 mm	Security		Rensington Slot			Humidity: 20% to 95%	
			IP St	treaming				
Resolution	1080p 60fps	Bit-Rate Range Setting 512 Kbps to 32 Mbps						
Network Video Compression Formats	H.264, MJPEG (Web Page)	Network Interface 10/100 Base-T						
Network Audio Compression	AAC	NDI® HX Capability N/A						
Formats		Multi-Stream Capability 2 (1 for IP Streaming, 1 for Web P 3 (1 for IP Streaming, 1 for Web P						
Sample Rates	48, 32, 16, 8 KHz	Network Protocols		IPv6, IPv4, TCP, UDP, ARP, ICMP, IGMP, HTTP, DHCP,				
Maximum Frame Rate	1080p 60fps	RTP / RTCP, RTSP, RTMP, VISCA over IP						
Bit-Rate Control Modes	VBR, CBR							
				USB				
Connector	USB 3.1 Gen 1 Type-B	Maximum Video Resolution		1080p	USB Audio Class	(UAC)	UAC 1.0	
Video Format	MJPEG, YUY2	USB Video Class (UVC)		UVC 1.1				
			W	/eb UI				
Live Video Preview	Yes	Camera/Image Adjus	tment	Exposure, White Balance, Picture	Network Configur	ation	DHCP, IP Address, Gateway	
Ourse DTZ Ourstaal	Den Tilt Zeens Freue Durect			•			Subnet Mask, DNS	
Camera PTZ Control	Pan, Tilt, Zoom, Focus, Preset Control							
			Softw	vare Tools				
IP Search and Configuration	Supports Windows® 7 or later	PTZ Control Panel	ol Panel Supports iPadOS® 9 or later					
Tool PTZ Management	Supports Windows® 7 or later	CaptureShare Supports Windows® 7 or later, macOS® 10.14 or later						
			Wa	arranty				
Camera	3 Years	Accessories		1 Year				
			Packag	je Contents				
Package Contents	Camera, Remote Control, Power Adapter, Power Cord, USB Cable, Cable Ties (x4), Cable Fixing Plate (x1), M2 x 4mm Screws (x2), 1/4"-20L 7.5mm Screw (x1), Quick Start Guide							
Optional Accessories	Wall Mount Brackets (x2), M4 x 8mm Screw (x2), 1/4"-20L 7.5mm Screw (x1), Wall Mount Kit, Installation Guide, Ceiling Mount Brackets (x2), M3 x 6mm Screws (x3), 1/4"- 20L 7.5mm Screws (x3), Ceiling Mount Kit Installation Guide							
			Orde	ring Info				
Part Number	PAVPTDL30							

* Specifications may vary depending on location and are subject to change without notice.



AVer Information Inc. Americas averusa.com. 668 Mission Court, Fremont, CA 94539 T:408.263.3828 F:408.263.8132 Toll free:1.877.528.7824 ©Copyright 2021, AVer Information Inc. All rights reserved. Specifications subject to change without notice.